


Internal Door Type Elevations
1 : 20


Internal Door Schedule								
Mark	Type Mark	Width	Height	Fire Rating (minutes)	Smoke Seals	Acoustic Rating (dB Rw)	Finger Protection	Comments
IDG01	Type D	1150	2110	0	No	30	Yes	Controlled access, key pad from lobby with override on nursery side
IDG02	Type K	910	2110					Lockable with internal thumbturn
IDG03	Type B	1010	2110	30	No	30	Yes	Lockable with internal thumbturn
IDG04	Type A	1010	2110	30	Yes	35	Yes	Blinds required, spec N10/240
IDG05	Type A	1010	2110	30	Yes	30	Yes	Controlled access, key pad from corridor with override on nursery side
IDG06	Type C	3270	2090					To be lockable
IDG07	Type A	1010	2110					To be lockable
IDG08	Type A	1010	2110	30	Yes	30	No	Lockable with internal thumbturn
IDG09	Type B	1010	2110	0	No	30	No	Bathroom cylinder and turn
IDG10	Type B	1010	2110					Lockable with internal thumbturn
IDG11	Type A	1010	2110	30	No	30	No	Lockable with internal thumbturn
IDG12	Type E	Site measure	Site measure	60	Yes	35	Yes	Controlled access, key pad from lobby with override on nursery side
IDG13	Type E	Site measure	Site measure	60	Yes	35		Lockable with internal thumbturn
								To Room: Name
								Nursery Room 2
								Kitchenette
								Store
								Sleep Room
								Circulation
								Nursery Room 1
								Nursery Room 1
								Utility / Cleaners
								Acc WC
								Nursery Room 1
								Child WC / Baby Change 1
								Nursery Room 2
								Lobby

Existing Internal Door Schedule				
Mark	Width	Height	Finger Protection	Comments
XID01	910	2110	No	To be lockable
XID02	910	2110	Yes - to be added	
XID03	910	2110		To be demolished
XID04	1500	2110		To be demolished
XID05	910	2110		To be demolished
XID06	810	2110		To be demolished
XID07	810	2110		To be demolished
XID08	810	2110		To be demolished
XID09	810	2110		To be demolished
XID10	1500	2110		To be demolished
XID11	910	2110		To be demolished




Typical Ironmongery and Vision Panel Positions

Internal Doors - Ironmongery Locations
1 : 20



Typical Internal Door Head
1 : 10

Internal Door Ironmongery Schedule																																														
Mark	Type Mark	Room	Fire Rating (minutes)	Smoke Seals	CE MARKED BB BUTT HINGE TO BS EN 1935	MONO-AMMONIUM PHOSPHATE HINGE PAD TO SUIT ABOVE FOR FD30 APPLICATION	MONO-AMMONIUM PHOSPHATE HINGE PAD TO SUIT ABOVE FOR FD60 APPLICATION	SIZE 2-4 ADJUSTABLE OVERHEAD CLOSER TO BS EN 1554 CE MARKED	SAPA 202 - 188 EA CONCEALED DOOR CLOSER	DIN STANDARD E/P DEADLOCK TO BS EN 12209 AND CE MARKE	DIN STANDARD E/P SASHLOCK TO BS EN 12209 AND CE MARKED	ADAMS RITE 4750 DEADLATCH WITH EXTERNAL KEY & EUROPROFINE CYLINDER	MONO-AMMONIUM PHOSPHATE PACK TO SUIT ABOVE FOR FD30 APPLICATION	MONO-AMMONIUM PHOSPHATE PACK TO SUIT ABOVE FOR FD60 APPLICATION	FLAT PATTERN LATCH TO BS EN 12209 CE MARKED	INTUMESCENT PACK TO SUIT ABOVE FOR FD30 APPLICATION	35/35 CYLINDER/THUMB TURN	40MM 1/2 CYLINDER	PULL HANDLE - 450MM LENGTH SUITABLE FOR EQUALITY ACT APPLICATIONS	500X75MM FINGER PLATE RADIUS CORNERS SSS	RTD LEVER HANDLE ON ROSE TO BS EN 1906 SSS	BATHROOM TURN AND RELEASE SSS FOR EQUALITY ACT APPLICATION	E/P ESCUTCHEON IN SSS	KICKPLATE TO NOMINAL SIZE - TBC BEFORE ORDERING	INTUMESCENT FIRE AND SMOKE STRIP WHITE	INTUMESCENT FIRE ONLY STRIPE WHITE	FIRE DOOR KEEP SHUT SIGN	FIRE DOOR KEEP LOCKED	FINGER TRAP PROTECTION TO BOTH SIDES OF DOOR	DIGITAL KEYPAD FOR DOOR ACCESS	7100 SERIES ELECTRIS STRIKE	FACE-TO-FACE MAGNET FOR TOP OF DOOR	KEY OVERRIDE AND TEST BOX WITH 1/2 CYL. UMK	GREEN BOX FOR WALL MOUNTING / EMERGENCY DOOR OVERRIDE	DOOR EXIT BUTTON	DOOR CONTROLLER	CALL POINT FOR EXTERNAL DOOR	INTERNAL PHONE / RELEASE	4 LEAF BIFOLD IRONMONGERY PACK	CEILING RUNNING TRACK, NO FLOOR RAIL, ENDFOLD, SINGLE UNIT	FLUSH LEVER HANDLE WITH LATCH AND THUMB TURN LOCK					
IDG01	Type D	Lobby	0	No	1.5				1			1					1		1	1			1	2						1	1	1	1	1	1	1	1	1								
IDG02	Type K	Nursery Room 2																																												
IDG03	Type B	Nursery Room 2	30	No	1.5	6		1			1		1				1				1		1	2		2.5		2	1																	
IDG04	Type A	Nursery Room 2	30	Yes	1.5	6		1							1	1					1			1	2.5																					
IDG05	Type A	Nursery Room 2	30	Yes	1.5	6		1		1		1					1		1	1			1	1	2.5		2	1	1	1		1	1	1	1											
IDG06	Type C	Nursery Room 2																																												
IDG07	Type A	Circulation																																												
IDG08	Type A	Lobby	30	Yes	1.5	6		1			1		1				1				1		1	2	2.5		2																			
IDG09	Type B	Circulation	0	No	1.5																	1		2		2.5		2																		
IDG10	Type B	Staff WC																																												
IDG11	Type A	Nursery Room 1	30	No	1.5	6		1							1	1					1		1	2	2.5		2																			
IDG12	Type E	Lobby	60	Yes	1.5		6	1		1				1				1		1	1			1	2	2.5		2		1																
IDG13	Type E	Fitness Studio	60	Yes	1.5		6	1	1	1				1	1		1		1	1	1			1	2	2.5		2																		



Typical Internal Door Jamb
1 : 10

Responsibility is not accepted for errors made by others in scaling from this drawing.
All construction information should be taken from figured dimensions only.

0mm 50mm 100mm

Notes:

Doors to be laminate finish

Frames to be painted grey to match existing

Dulux high performance diamond eggshell

Colour to be specified

Manifestation to be added to all full height glazing in accordance with Approved Documents M and K.

Doors with Fire Rating and/or 'Smoke Seals' to be self closing. Where needed to be opened manually, the opening force at the leading edge of the door must not exceed 20N.

Dry lining installers to ensure plasterboard returns are incorporated into door jamb (and head) details without reducing the structural openings indicated.

D2	P34	08.06.2018	REISSUE FOR TENDER
D3	P30	29.01.2018	CONSTRUCTION ISSUE
D2	P29	11.01.18	Updated Ironmongery Schedule
D2	P26	15.11.2017	REISSUE FOR TENDER
D2	P24	13.11.2017	BUILDING CONTROL ISSUE
D2	P20	09.11.2017	TENDER ISSUE
S3	P18	24.10.2017	Building Control Issue
S3	P16	10.10.2017	First issue - For client comment and review
S0	P13	09.10.2017	WIP Issue for Co-ordination

STATUS	REV	DATE	DESCRIPTION	REVISED BY
CLIENT				KS
Council of the Isles of Scilly				CHECKED BY
				GF
				ORIGINATOR NO
				150457

CONSULTANT
STRIDE TREGLOWN
www.stridetreglown.com

PROJECT
Carn Gwavel
Church Road
St Mary's
Isles of Scilly
TR21 0NA

DRAWING TITLE
Internal Door Schedule

SUITABILITY STATUS D2 : SUITABLE FOR TENDER	SCALE As indicated @ A1
PROJECT ORIGINATOR ZONE LEVEL TYPE ROLE CLASSIFICATION NUMBER 150457-STL-XX-XX-DR-A-XXXX-71002	REVISION P34